



US. J21303A

United States Patent [19]

Terada et al.

[11] **Patent Number:** **6,021,303**[45] **Date of Patent:** **Feb. 1, 2000**[54] **IMAGE HEATING DEVICE AND IMAGE FORMING DEVICE USING THE SAME**

[75] Inventors: **Hiroshi Terada**, Ikoma; **Akinori Toyoda**; **Yoshihito Urata**, both of Katano; **Hajime Yamamoto**, Ikoma; **Nobuo Genji**, Osakasayama; **Naoaki Ishimaru**, Minoo; **Tatsuo Nakatsugawa**, Utsunomiya; **Masakazu Naito**, Shiyo-gun, all of Japan

[73] Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka, Japan

[21] Appl. No.: **09/309,922**[22] Filed: **May 11, 1999**[30] **Foreign Application Priority Data**

May 15, 1998 [JP] Japan 10-132984
Jul. 17, 1998 [JP] Japan 10-203005

[51] Int. Cl.⁷ **G03G 15/20**[52] U.S. Cl. **399/328; 399/329; 399/330; 399/335**[58] Field of Search **399/320, 328, 399/329, 330, 333, 335, 338**[56] **References Cited****U.S. PATENT DOCUMENTS**

4,256,945 3/1981 Carter et al. .
5,568,240 10/1996 Ohtsuka .

5,713,069 1/1998 Kato 399/330
5,752,148 5/1998 Yoneda et al. 399/329
5,765,086 6/1998 Kishino et al. 399/329
5,768,673 6/1998 Morigami 399/330
5,778,293 7/1998 Ohtsuka .
5,822,669 10/1998 Okabayashi et al. 399/330
5,862,445 1/1999 Ogawa et al. 399/329
5,881,349 3/1999 Nanataki et al. 399/328
5,939,337 8/1999 Hatakeyama et al. 399/335 X
5,940,655 8/1999 Sano et al. 399/328 X

Primary Examiner—Sandra Brase*Attorney, Agent, or Firm*—Merchant & Gould, P.C.

[57]

ABSTRACT

An image heating device comprises a cylindrical heating roller with a Curie temperature of 210° C., a magnetization coil for magnetizing the heating roller with an alternating magnetic field, which is arranged inside the heating roller, and a nip portion for heating a recording material that carries a toner image with heat from the heating roller, while the recording material is being conveyed along said nip portion. The ratio between the amount of heat generated in said heat-generating member at Curie temperature or higher to the amount of heat generated at room temperature in said heat-generating member is not more than ½. With this configuration, the heating roller can regulate its own temperature to stabilize at a temperature that is suitable for fixing, and the problems of partial overheating or underheating, unstable heat generation, or damage of the device can be eliminated.

34 Claims, 10 Drawing Sheets